

Application No.: 09/870280

Docket No.: MWS-040RCE

**AMENDMENTS TO THE CLAIMS****RECEIVED  
CENTRAL FAX CENTER  
NOV 20 2006**

Upon entry of this amendment, the following listing of claims will replace all prior versions and listings of claims in the pending application.

Please amend the pending claims as follows:

1. (Previously presented) A computer implemented modeling process comprising:  
providing a plurality of blocks, each of the blocks representing functional entities;  
generating a plurality of output signal values from the plurality of blocks;  
grouping the plurality of output signal values as an ordered set in a multiplexer as a first composite signal; and  
outputting the first composite signal.
2. (Previously Presented) The process of claim 1 wherein each of the blocks includes at least one output signal port.
3. (Previously Presented) The process of claim 1 wherein a plurality of input signal values and the output signal values have at least one attribute.
4. (Original) The process of claim 3 wherein the attribute is a name.
5. (Original) The process of claim 3 wherein the attribute is a data type.
6. (Original) The process of claim 3 wherein the attribute is a numeric type.
7. (Original) The process of claim 3 wherein the attribute is a dimensionality.
8. (Original) The process of claim 1 wherein the ordered set is a linked list data structure.

Application No.: 09/870280

Docket No.: MWS-040RCE

9. (Currently Amended) The process of claim 8 wherein the linked list data structure is a tree data structure, the tree data structure including  $m + n$  nodes, wherein  $m$  represents a number of independent signals and  $n$  represents a number of composite signals.
10. (Cancelled)
11. (Original) The process of claim 1 further comprising:  
decomposing the first composite signal into the plurality of output signals in a demultiplexer.
12. (Original) The process of claim 1 further comprising viewing the ordered set contained in the first composite signal with a composite signal viewer.
13. (Original) The process of claim 1 wherein at least one of the input signal values is a second composite signal.
14. (Previously Presented) A block diagram modeling process comprising:  
providing a first block and a second block, the blocks representing functional entities;  
generating a plurality of output signal values from the first and second block;  
grouping the plurality of output signal values as an ordered set in a multiplexer as a first composite signal; and  
processing the composite signal in a third block.
15. (Original) The process of claim 14 wherein the ordered set is a linked list data structure.
16. (Previously Presented) The process of claim 14 wherein an input signal is a second composite signal.
17. (Previously Presented) The process of claim 14 further comprising decomposing the composite signal into a plurality of input signal values.

Application No.: 09/870280

Docket No.: MWS-040RCE

18. (Original) The process of claim 14 further comprising viewing the composite signal in a composite signal viewer.
19. (Original) The process of claim 18 wherein the composite signal viewer displays the ordered set contained in the composite signal on a graphical user interface (GUI).
20. (Original) The process of claim 19 wherein the GUI is provided on an input/output device.
21. (Previously Presented) A computer program product residing on a computer readable medium having instructions stored thereon which, when executed by the processor, cause the processor to:
  - provide a plurality of blocks, each of the blocks representing functional entities;
  - generate a plurality of output signal values from the plurality of blocks;
  - group the plurality of output signal values as an ordered set in a multiplexer as a first composite signal; and
  - output the first composite signal.
22. (Original) The computer program product of claim 21 wherein the computer readable medium is a random access memory (RAM).
23. (Original) The computer program product of claim 21 wherein the computer readable medium is read only memory (ROM).
24. (Original) The computer program product of claim 21 wherein the computer readable medium is hard disk drive.
25. (Previously Presented) A processor and a memory configured to:
  - provide a plurality of blocks, each of the blocks representing functional entities;
  - generate a plurality of output signal values from the plurality of blocks;
  - group the plurality of output signal values as an ordered set in a multiplexer as a first composite signal; and
  - output the first composite signal.

Application No.: 09/870280

Docket No.: MWS-040RCE

26. (Original) The processor and memory of claim 25 wherein the processor and the memory are incorporated into a personal computer.
27. (Original) The processor and memory of claim 25 wherein the processor and the memory are incorporated into a network server residing in the Internet.
28. (Original) The processor and memory of claim 25 wherein the processor and the memory are incorporated into a single board computer.
29. (Previously Presented) A computer implemented modeling process comprising:  
    providing a plurality of blocks, each of the blocks representing a functional entity that generates one or more output signals;  
    grouping the output signals as an ordered set in a multiplexer as a composite signal; and  
    outputting the composite signal.
30. (Original) The process of claim 29 wherein the ordered set is a tree data structure.
31. (Original) The process of claim 30 wherein the tree data structure is a linked list.
32. (Original) The process of claim 29 further comprising:  
    providing a composite signal viewer; and  
    viewing the ordered set in a graphical user interface executing in the composite signal viewer.
33. (Previously Presented) A computer program product residing on a computer readable medium having instructions stored thereon which, when executed by the processor, cause the processor to:  
    provide a plurality of blocks, each of the blocks representing a functional entity that generates one or more output signal values;

Application No.: 09/870280

Docket No.: MWS-040RCE

- group the output signals as an ordered set in a multiplexer as a composite signal;  
and output the composite signal.
34. (Previously Presented) A processor and memory configured to  
provide a plurality of blocks, each of the blocks representing a functional entity  
that generates one or more output signal values;  
group the output signals as an ordered set in a multiplexer as a composite signal;  
and  
output the composite signal.
35. (Previously Presented) A method for providing a composite signal in a modeling  
environment, the method comprising the steps of:  
providing a plurality of output signals from one or more blocks;  
generating a composite signal comprising a set of the plurality of output signals; and  
providing the composite signal as an output signal.
36. (Previously Presented) A method for graphically representing a composite signal in a  
modeling environment, the method comprising the steps of :  
providing a plurality of output signals from one or more blocks, each output signal  
graphically indicated by a signal identifier; and  
providing a composite signal identifier to graphically indicate a grouping of signal  
identifiers, the composite signal identifier representing a composite signal comprising a set of  
the plurality of output signals.